


SE-SS Range - Input/output modules



Optocoupled input and output modules for control interface. Plug-in relay solution.




PRODUCT REFERENCE	Input Voltage	Input R	Logic Voltage	Output	Specifications	Dimensions mm
SEA05020	180-280VAC/DC	54 kΩ	5VDC (3-8V)	NPN 25mA	AC/DC Input	44 x 15 x 33
SEA24020	180-280VAC/DC	54 kΩ	24VDC (15-30V)	NPN 25mA	AC/DC Input	
SEC05003	10-32 VDC	1 kΩ	5VDC (3-8V)	NPN 25mA	DC input	
SEC05103	10-32 VDC	1 kΩ	5VDC (3-8V)	NPN 25mA	DC quick input	
SEC24003	10-32 VDC	1 kΩ	24VDC (15-30V)	NPN 25mA	DC input	

PRODUCT REFERENCE	Switching Current	Switching Voltage	Control Voltage	Input R	Specifications	Dimensions mm
SSA05320	3A	12-280VAC	5VDC (3-8V)	220 Ω	AC output	44 x 15 x 33
SSA24320	3A	24-280VAC	24VDC (15-30V)	2200 Ω	AC output	
SSC05306	3A	3-60 VDC	5VDC (3-8V)	220 Ω	AC output	
SSC24306	3A	3-60 VDC	24VDC (15-30V)	2200 Ω	AC output	
EBS01000	DIN rail Base for input/output Module					

Only the most common references are given in these tables. Other products with different voltages are available : please contact us.

XK Range

Suffix D :
removable terminals



Interface relays to control loads such as resistors, indicators, solenoids, transformers, motors, power contactor coils. These DIN-rail mounted products come in AC, DC outputs and three phase motor control : 2 and 3 phase switching and rotation reverser. Fitted with LED.

PRODUCT REFERENCE	Switching Current	Switching Voltage	Control Voltage	Input R	Protec.	Specifications	Dimensions mm	Fig n°
XKA20420	4A	12-275VAC	6-30VDC	1 kΩ	VDR	1 pole AC synchronous output	12,2x76,4x53	1
XKA70420	4A	12-275VAC	15-30VAC/DC	1800 Ω	VDR	1 pole AC synchronous output	17,2x76,4x53	1
XKA70440	4A	12-440VAC	15-30VAC/DC	1800 Ω	VDR	1 pole AC synchronous output	17,2x76,4x53	1
XKA90440	4A	12-440VAC	150-240VAC/DC	41 kΩ	VDR	1 pole AC synchronous output	17,2x76,4x53	1
XKD10120	1A	2-200VDC	5-30VDC	1 kΩ	diode	1 pole DC output	12,2x76,4x53	1
XKD10306	3A	2-60VDC	5-30VDC	1 kΩ	diode	1 pole DC output	12,2x76,4x53	1
XKD11306D	3A	2-60VDC	3-30VDC	600 Ω	diode	1 pole DC output	12,2x76,4x53	1
XKD70306	3A	2-60VDC	10-30VAC/DC	1800 Ω	diode	1 pole DC output	12,2x76,4x53	1
XKD90306	3A	2-60VDC	90-240VAC	41 kΩ	diode	1 pole DC output	17,2x76,4x53	1
XKH20120	10A	12-280VAC	10-32VDC	1640 Ω		1 pole AC synchronous output	25x76,4x65	3
XKM22440	4AC-51/2,5AC-53	24-460VAC	15-40VDC	2 kΩ	VDR	2 pole motor switching control	25,2x76,4x53	2
XKM23440	4AC-51/2,5AC-53	24-460VAC	12-35VDC	1 kΩ	VDR	3 pole motor switching control	47,5x76,4x53	4
XKR24440	4AC-51/2,5AC-53	24-460VAC	15-40VDC	2 kΩ	VDR	Motor change-over control	58,2x76,4x53	4

Other references available : please consult us.

XKM23 : 3 relays
XKM24 : 4 relays